Chevron MUSE Collection



Type of flooring:

Wood boards: Engineered parquet wood flooring

Species: European Oak

Latin name: Quercus Mongolica

Sub-structure: Eucalyptus & Birch/Pure Birch 7-9 layers cross lay

Adhesive: Franklin USA

Appearance: 1, Grade AB, clean surface with nearly no timber knots

2, Giant size grade, clean surface with rare knots

Board size: 1, 15mm thick x 125 mm wide x 680 mm long with a 3mm solid oak

top layer of cut Veneer

Angel: Vertical 45 degree

Strips: One

Edges: Micro-bevelled 0.3mm

Finish: Matt Lacquered

Surface: Brushed, stained

Joint system: Tongue & Groove

Application: Normal residential & moderate commercial use

Underfloor heating: Yes

Re-sand able: Yes

Colour Ranges as below, may changes when new colours come in.















PERFORMANCE:

Assessed property	Classification or test method	Requirement	Result or classification	Evaluation
Release of formaldehyde	EN 717-1	≤0.124 mg/m3	≤0.014 mg/m3	E0
Width-permit deviation	EN 13647	±0.2mm	-0.1mm	Fulfil
Moisture content	EN 13183-1	9±2%	7.0%	Fulfil
Reaction to fire(floor)	AS ISO 9239.1-2003	CRF≥4.5KW/m2	6.9 KW/m2	Fulfil
Reaction to fire (wall& ceiling)	AS/NZS 3837:1998	Group number 1-4	Group number 3	Middle range
Sliptest-Wet Pendulum	AS 4586&4663 (2013)	P1-P5	P2	Middle range
Hardness	Janka Rating	None	1360	Middle range

For test report information, please contact style timber office

[©] This fact sheet is belong to style timber floor Pty Ltd. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless style timber floor has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.