## STYLETIMBER

## SUPER PLANK



## Types of flooring:

Wood boards: Engineered parquet wood flooring

Species: Oak

Latin name: Quercus Mongolica

Sub-sturcture: Eucalyptus & Birch/Pure Birch 10-13 layers cross lay 14mm

Adhesive: Dynea

Appearance: 1, Grade ABCD, clean surface with standard knots

Board size: 1, 20 mm thick with a 6mm solid oak top layer of cut veneer, 300-

500mm wide, 3000 mm to 5000mm long

Strips: One

Pack size: 2 pieces per carton.

Edges: Micro-bevelled 0.5mm

Finish: Unfinished, Raw oak

Surface: Uncoated

Joint system: Tongue & Groove

Application: Residential & moderate commercial use

Underfloor heating: Yes

Re-sand able: Yes

## PERFORMANCE:

Assessed property	Classification or test method	Requirement	Result or classification	Evaluation
Release of formaldehyde	EN 717-1	≤0.124 mg/m3	≤0.014 mg/m3	E0
Width-permit deviation	EN 13647	±0.2mm	-0.1mm	Fulfil
Moisture content	EN 13183-1	9±2%	7.0%	Fulfil
Reaction to fire(floor)	AS ISO 9239.1-2003	CRF≥4.5KW/m2	6.9 KW/m2	Fulfil
Reaction to fire (wall& ceiling)	AS/NZS 3837:1998	Group number 1-4	Group number 3	Middle range
Sliptest-Wet Pendulum	AS 4586&4663 (2013)	P1-P5	P2	Middle range
Hardness	Janka Rating	None	1360	Middle range

For test report information, please contact style timber office

<sup>©</sup> This fact sheet is belong to style timber floor Pty Ltd. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless style timber floor has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.